








Sandwich-Paneele S – Übersicht

Stahl/PUR/Stahl¹⁾

Profilskizzen	Technische Werte	Typenbezeichnung KAS- ²⁾	Profilhöhe d mm	Schaumdicke s mm	Gewicht g daN/m ²	U-Wert W/m ² K	Deckschalen Varianten					
							LL	GL	PL	ML	VL	
		W- 40-1150-LL-S	40	40	11,60	0,57	•	•	•		a.A. ³⁾	
		W- 60-1150-LL-S	60	60	12,50	0,39	•	•	•		a.A. ³⁾	
		W- 80-1150-LL-S	80	80	13,30	0,30	•	•	•		a.A. ³⁾	
		W- 100-1150-LL-S	100	100	14,10	0,24	•	•			a.A. ³⁾	
		W- 120-1150-LL-S	120	120	14,90	0,20	•	•			a.A. ³⁾	
		W- 150-1150-LL-S	150	150	16,10	0,16	•	•			a.A. ³⁾	
		W- 180-1150-LL-S	180	180	17,30	0,14	nur auf Anfrage					
							LL	GL	RL	ML	VL	
	KAS Wandpaneel	unsichtbar befestigt	WB- 60-1000-LL-S	60	60	12,60	0,39	•	•	•	•	a.A. ³⁾
			WB- 80-1000-LL-S	80	80	13,40	0,30	•	•	•	•	a.A. ³⁾
			WB- 100-1000-LL-S	100	100	14,02	0,24	•	•	•	•	a.A. ³⁾
	KAS Wandpaneel	unsichtbar befestigt	WB- 60-600-LL-S	60	60	13,50	0,39	•	•	•	•	a.A. ³⁾
			WB- 80-600-LL-S	80	80	14,30	0,30	•	•	•	•	a.A. ³⁾
			WB- 100-600-LL-S	100	100	15,10	0,24	•	•	•	•	a.A. ³⁾
							SL					
	KAS Wandpaneel Welle 18/77	WS- 80-1000-SL-S	78	60	13,90	0,34	•					
							TL					
	KAS Wandpaneel	W-75-1020-TL-S	75	40	12,80	0,40	•					
		W-95-1020-TL-S	95	60	13,60	0,30	•					
							TL					
	KAS Dachprofil	D- 65-1000-TL-S	65	30	12,70	0,61	•					
		D- 75-1000-TL-S	75	40	13,10	0,48	•					
		D- 95-1000-TL-S	95	60	13,90	0,34	•					
		D- 115-1000-TL-S	115	80	14,70	0,27	•					

¹⁾ Alle Sandwich-Paneele mit Stahldeckschalen außen 0,63 mm, innen 0,50 mm und einem Polyurethanhartschaumkern (PUR) FCKW-frei.

²⁾ W-40-1150-LL-S

³⁾ a.A. = auf Anfrage

